

PRODUCT DATA SHEET

FLEXO ELO THINNER

DESCRIPTION	83060-0960 Alcohol/Ester/Glycol Ether
USE based	This product is a solvent mixture used in a wide variety of solvent printing inks. Please refer to Data Sheet of the ink series to confirm that it is appropriate. Can also be used for cleaning the printing press.

TECHNICAL INFORMATION AND HANDLING

SPECIFY GRAVITY	0.815
FLASH POINT	-5.0°C Lowest present in the mixture
EVAPORATION RATE (Ether = 1)	2.9 Lowest present in the mixture
SAFETY PRECAUTIONS	Highly flammable liquid. Keep away from heat, sparks and flame Keep out of reach of children Avoid breathing vapour- ensure full ventilation while thinning, applying and cleaning. Keep containers upright and closed when not in use to prevent leakage. In case of skin contact wash thoroughly with soap and water. In case of eye contact flush immediately and call physician. If swallowed, call physician immediately. Do not induce vomiting.

This information has been carefully compiled from experienced gained in field conditions and detailed laboratory testing. However, the product's performance and its suitability for the customer's purpose depend on the particular conditions of use and the material being printed. We recommend that customers satisfy themselves that each product meets their requirements in all respects before commencing a print run. Since we cannot anticipate or control the conditions under which our products are used it is not possible to guarantee their performance. We would point out that the information contained in this leaflet is only a recommendation and may need to be altered to suit the conditions and efficiency of the equipment employed. Our products are not designed for use in conjunction with those of any other ink maker or similar supplier unless agreed to in writing. All sales are subject of our standard terms and conditions of sale

December 2004