

PRODUCT DATA SHEET

FLEXO POLYSACK 83238

SOLVENT BASED FLEXOGRAPHIC INKS

FLEXO POLYSACK is a range of solvent-based inks for flexo printing for use on Woven Polypropylene.
FLEXO POLYSACK Inks exhibit excellent print quality and adhesion.

PROPERTIES Good gloss
 Controlled coefficient of friction.
 Good scuff resistance.
 Chrome free.

TECHNICAL INFORMATION AND INK HANDLING

SUBSTRATES Woven Propylene sacks (fertilizers, chemicals etc.).
 please refer to our technical department for further details.

REDUCTION Normal reducer - 83060-1026

No guarantees for our ink can be given if the above solvent reduction is not followed. The use of other solvents and solvent blends are known to cause problems such as blocking, odour and reduced bond strength. In extremely severe cases the wrong solvent can cause "Ink Chunk Out".

WASH UP 83060-1026

ROLLERS AND STEREO flexo roll coverings and stereos should be hydrocarbon solvent resistant.

- PRESS SPEEDS** The inks are formulated to print at low or at higher speeds on reel-to-reel sack presses.
- COLOUR RANGE** FLEXO POLYSACK inks are available in a wide range of colours. Occasionally limited by pigment selection suitable for specified requirements. Pigments used have reasonable light fastness but may not be suitable for direct exposure to sunlight. Please discuss with our technical service personnel your actual requirements.
- STORAGE** Keep the container tightly closed.
Do not expose to the direct sunlight.
Keep the container in well-ventilated place.

This information has been carefully compiled from experienced gained in field conditions and detailed laboratory testing. However, the product's performance and its suitability for the customer's purpose depend on the particular conditions of use and the material being printed. We recommend that customers satisfy themselves that each product meets their requirements in all respects before commencing a print run. Since we cannot anticipate or control the conditions under which our products are used it is not possible to guarantee their performance.

We would point out that the information contained in this leaflet is only a recommendation and may need to be altered to suit the conditions and efficiency of the equipment employed. Our products are not designed for use in conjunction with those of any other ink maker or similar supplier unless agreed to in writing. All sales are subject of our standard terms and conditions of sale.

November 2004